

## “LaCygne Polymeric Specifications”

Rev 1 – Dated: 10/23/2017

Written By: IA

Approved by: VP/JV

Pages 1 of 1

Sieve Size	Minimum	Maximum
<b>US#8</b>	<b>0.0%</b>	<b>0.0%</b>
<b>US #16</b>	<b>5.0%</b>	<b>25%</b>
<b>US #30</b>	<b>15.0%</b>	<b>25.0%</b>
<b>US #50</b>	<b>30.0%</b>	<b>36.0%</b>
<b>US #100</b>	<b>15.0%</b>	<b>29.0%</b>
<b>US #200</b>	<b>5.0%</b>	<b>14.0%</b>
<b>Pan</b>	<b>0.0%</b>	<b>1.0%</b>

- Do NOT apply oil
- Above % retained was driven from the following % passing cust' spec:

	Input Values	Input Values	
Sieve	MIN % Passing	MAX % Passing	Retained % Spec. Based on Min & Max % Passing
8	100.0%	100.0%	0% 0%
16	75.0%	95.0%	5% 25%
30	50.0%	80.0%	15% 25%
50	20.0%	44.0%	36% 30%
100	5.0%	15.0%	29% 15%
200	0.0%	1.0%	14% 5%
PAN			1% 0%